13-14 HP | 18.4 cfm Engine Driven Air Compressor

Options









18.4 cfm @ 175 psi

24.3 cfm @ 90 psi

Features

- Easy use pump oil drain
- Easy view oil sight glass
- Electric start drive engine
- Engine idle control for fuel savings
- Engine has recharging system
- Fork slot width mounting feet for more stable base and more maneuverability
- Inline pump for smooth operation
- Low rpm pump for lower operating temperature
- Operating pressures available up to 190 psi
- OSHA compliant belt guard
- Oversized pump flywheel for better pump cooling
- Pilot valve for continuous operation
- Solid cast iron pump
- Stainless steel flexible 1200° F rated air line
- Swedish steel reed valves
- Vibration isolation mount included
- 2-stage compressor pump
- 2-piece tank design for more mounting options of compressor system
- 30 Gallon ASME/CRN Air Receiver
- A. Electric start drive engine with recharge capabilities for a battery
- B. Stainless steel flexible air line rated for over 1200°F provide more cooling and a longer life span for the package
- C. Pneumatic Throttle Control
- D. 2 piece tank design for more mounting options and vibration reduction pads
- E. Wide solid weld mounting feet for easier mounting, stability, and longer life span.

Belt guard after cooler
Remote starting system (Kohler Only)

Battery mounted and wired

A
Louiside on Polit To the State of the State
COS STEELS

Model	HP	Tank	Drive Engine	Length	Width	Height	Weight	cfm @ 90 psi	cfm @ 175 psi
C130GEH33	13	30 Gallon	Honda GX390	42	22	42	395 lbs	24.3	18.4
C140GEH33	14	30 Gallon	Kohler CH440	42	22	42	395 lbs	24.3	18.4

No Start Up Kit Required

Optional 5-year Pump Warranty Available

See catalog for additional options

Compressed Air Systems

Simplicity. It's What We Do.





