www.CompressedAirSystems.com 19 CFM Gas Compressor/Generator/Welder

Basic Compressor

Features

- Heavy Duty two stage solid cast iron pump
- Disk and spring valves
- Bearings on both ends of the crank shaft
- Centrifugal unloader
- Needle bearings, and inserts on rods
- Industrial grade gas engine
- ASME tested powder coated steel tank
- 2 grove B width motor pulley
- Access to compressor valves without compressor head removal
- Pilot valve continuous operation
- Fully enclosed belt guard
- Full saddle mounting feet instead of pegged mounting feet

- Alternator on driven engine
- 5500 Watt Generator
- 110/220 Volt Outlets
- 41 Amps @ 120 Volt
- 20 Amps @ 240 Volt
- Belt guard after cooler
- On-board battery mounted and wired (No wiring to the front of the truck
- Automatic tank drain
- Vibration pads
- Freight pre-paid in the 48 states & southern Canada

19 CFM @ 175 PSI **5500 Watts** 250 Amp Welder





Model	HP	Mount	Tank	Drive Engine	Length	Width	Height	Weight
P130GEH8-WG	13	Tank	8 Gallon Horizontal	Honda Electric Start	46	26	42	550

No Start Up Kit Required

Optional 5-year Pump Warranty Available. See catalog for additional options.



Simplicity. It's What We Do. www.compressed-air-systems.com

