## 7.5 HP Reciprocating



24 cfm @ 175 psi



## **Basic Compressor Features**

- Access to compressor valves without compressor head removal
- All UL electrical controls
- ASME tested powder coated steel tank
- Auto start stop
- Bearings on both ends of the crank shaft
- Centrifugal unloader
- Disk and spring valves
- Fully enclosed belt guard
- Heavy-duty air filter
- Heavy-duty two stage solid cast iron pump
- Industrial grade electric motor
- Magnetic starter mounted and wired
- Needle bearings, and inserts on rods
- Stainless steel flex air lines
- Swedish steel valves
- TEFC drive motor (3 phase only)
- Torrington needle bearings
- 2-grove B width motor pulley
- 2-piece tank top plate design

## **Elite Compressor Features**

- All basic features
- Automatic tank drain
- Belt guard after cooler
- Low oil monitor
- Tank discharge ball valve
- Vibration pads
- Freight pre-paid in the 48 states & southern Canada



Model	Phase	Voltage	Tank	Length	Width	Height	Amp Draw 230 Volt	Amp Draw 480 Volt
B71V84	1	208-230	80 Gallon Vertical	32	26	78	32	N/A
B73V84	3	208-230-460	80 Gallon Vertical	32	26	78	18	9
B71H84	1	208-230	80 Gallon Horizontal	63	24	45	32	N/A
B73H84	3	208-230-460	80 Gallon Horizontal	63	24	45	18	9
B71V124	1	208-230	120 Gallon Vertical	42	34	84	32	N/A
B73V124	3	208-230-460	120 Gallon Vertical	42	34	84	18	9
B71H124	1	208-230	120 Gallon Horizontal	70	26	45	32	N/A
B73H124	3	208-230-460	120 Gallon Horizontal	70	26	45	18	9
Add E after part number to make Elite Model								

No Start Up Kit Required

**Optional 5-year Pump Warranty Available** 

See catalog for additional options

## **Compressed Air Systems**

Simplicity. It's What We Do.





