

Halogenated Hydrocarbon Scrubber

- ▲ Ideal for removing halogenated hydrocarbons from compressed air
- ▲ Extended-life adsorbent requiring minimal maintenance
- ▲ Protects equipment from chlorinated solvent vapors
- ▲ Purifies bulk inert non-corrosive gases



Parker Balston® Model 76080
Halogenated Hydrocarbon Scrubber

Parker Balston® Halogenated Hydrocarbon Scrubbers effectively remove halogenated hydrocarbons from an existing compressed air supply. The scrubber can be used with any Parker Balston Zero Air Generator or UHP Nitrogen Generator if the compressed air supply contains halogenated hydrocarbons. Halogenated hydrocarbons can corrode piping, filters, valves, and other components.

Principal Specifications

Model 76080 Halogenated Hydrocarbon Scrubber

Min/Max Pressure Rating	60 psig to 125 psig (4 barg - 8.6 barg)
Inlet/Outlet Ports	1/4" NPT (female)
Change Frequency @ 17 LPM	18 Months
Dimensions	41"h x 15"w x 8"d (104 cm x 38 cm x 20 cm)
Shipping Weight	29 lbs. (13 kg)

Ordering Information

Description	Model Number
Halogenated Hydrocarbon Scrubber (New)	76080