



9303 Stannum Street, Tampa, FL 33619 - P: +1 800-626-8177

---

# CAS-6061-150

## Synthetic Food Grade Compressor Lubricant

---

CAS-6061-150 synthetic food-grade compressor lubricant contains high-performance fluids and is designed for extended drain intervals. This lubricant meets H1 requirements for lubricants with incidental food contact (FDA 21 CFR 178.3570).

### ATTRIBUTES

---

- 4,000–6,000 hours of oil life at 100°C discharge temperature
- Meets H1 requirements for incidental food contact (FDA 21 CFR 178.3570)
- NSF-approved formulation
- Oxidatively stable
- Resists water contamination
- Protects against rust and corrosion
- Controls carbon and varnish formation
- Protects against wear
- Low volatility
- Excellent film strength
- High flash point
- Non-toxic/non-hazardous

### TYPICAL LUBRICANT PROPERTIES

---

<b>CAS-6061-150 Grades</b>	<b>150</b>
Viscosity cSt @ 40°C	150.4
Viscosity cSt @ 100°C	16.1
Viscosity Index	112
Flash Point °F (°C)	505 (263)
Copper Corrosion, 24 Hr	1a
Demulsibility, 130°F, 30 Min	40/40/0
Rust Test: Distilled Water	Pass
Rust Test: Salt Water	Pass
Foam Sequence I, II, III	0/0/0