

## Portable Compressors

# Mobilair™ M55PE



### Versatile

The Mobilair™ M55PE portable rotary screw compressor delivers 185 cfm at 100 psig and is designed for heavy-duty civil and commercial construction, demolition, sand blasting, and other site work applications as well as portable backup for stationary units.

### Low operating costs

The combination of our Sigma Profile airend and the proven Kubota Tier 4 Final diesel engine delivers superior fuel economy and reliability. Add in our large (21 gal) fuel tank and the M55PE is ready for full shift run time – up to 8 continuous hours without refueling.

### Safe road and site handling

On road or off, the M55PE offers superior handling with 15” wheels for higher ground clearance and a rigid tow bar with adjustable hitch height. High visibility, low energy LED lighting and heavy duty bumpers promote safety and protection. A convenient lifting eye aids in truck loading/unloading as well as in the service shop.

### All weather reliability

The M55PE features a high efficiency cooling system for operations in high heat conditions (up to 122°F). The high capacity cold-start battery ensures starts in cold weather and our exclusive anti-frost valve maintains optimal air temperature to prevent tool freeze up.

### Standard features:

- Energy efficient Sigma Profile airend
- Reliable Kubota Tier 4 Final diesel engine
- High capacity cold start battery
- Extra-large fuel tank
- Sigma Control Smart
- Two 3/4” Chicago and 1” NPT connections
- 15” wheels - higher ground clearance
- Rigid, height adjustable tow bar
- Lifting eye
- Heavy duty bumpers
- LED lighting kit
- Anti-frost valve

### Options:

- 145 psig model
- Aftercooler package
- Five year airend warranty

### Sigma Control Smart

The on-board controller ensures reliable and efficient operations with touch button control. Pressure adjustments are simple. Maintenance reminders and the operating/service history alerts your service team to any required service.

# Technical Specifications

COMPRESSOR		DIESEL ENGINE				PACKAGE			DIMENSIONS
Model	Free Air Delivery at 100 psig*	Make	Power @ Full Load (hp)	Full Load Speed (rpm)	Off Load Running Speed (rpm)	Fuel Tank Capacity (gal)	Weight (lb.)	Outlets	L** x W x H (in.)
M55PE	185 cfm	Kubota D1803CR-T Tier 4 Final	43	2300 - 2700	2100	21	1920	2 x 3/4" / 1 x 1"	113 x 61 x 58

\* Max pressure: 125 psig (145 psig model available)

\*\*Length includes tow bar

Sound level maximum is 76 db(A) at 23 feet.

Specifications are subject to change without notice.

## Advantages At a Glance:

- All weather operation
- Superior fuel economy
- Longer run time before re-fueling
- Scratch/dent resistance polyethylene cover
- Gull wing doors for easy service access
- PM reminders and service history
- Excellent on/off road handling and safety
- Easy pressure adjustment
- Low noise



## Optional 5 Year Warranty

To protect your investment, all of our Mobilair compressors are available with an optional 5 year warranty on the compressor airend.

**KAESER COMPRESSORS**®  
Built for a lifetime.



[www.kaeser.com](http://www.kaeser.com)

**Kaeser Compressors, Inc.**  
511 Sigma Drive  
Fredericksburg, VA 22408 USA  
Telephone: 540-898-5500  
Toll Free: 800-777-7873  
info.usa@kaeser.com

**Kaeser Compressors Canada Inc.**  
3760 La Vérendrye Street  
Boisbriand, QC J7H 1R5 CANADA  
Telephone: (450) 971-1414  
Toll free: (800) 477-1416  
info.canada@kaeser.com

**Kaeser Compresores de México S de RL de CV**  
Calle 2 #123  
Parque Industrial Jurídica  
76100 Querétaro, Qro.  
Telephone: 01 (442) 218 64 48  
sales.mexico@kaeser.com

**Kaeser Compresores de Guatemala y Cia. Ltda.**  
Calz. Atanasio Tzul 21-00, zona 12  
El Cortijo II, Bodega 501  
01012-Guatemala City  
Telephone: +502 2412-6000  
info.guatemala@kaeser.com

